




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B66C 23/72	A1	(11) International Publication Number: WO 98/15487 (43) International Publication Date: 16 April 1998 (16.04.98)
(21) International Application Number: PCT/SE97/00912 (22) International Filing Date: 28 May 1997 (28.05.97) (30) Priority Data: 9602158-9 9 October 1996 (09.10.96) SE (71)(72) Applicant and Inventor: VESTIN, Karl, Helge [SE/SE]; Olsborgsvägen 20, S-186 41 Vallentuna (SE).	(81) Designated States: AL, AU, BA, BB, BG, BR, CA, CN, CU, CZ, EE, GE, GH, HU, IL, IS, JP, KP, KR, LC, LK, LR, LT, LV, MG, MK, MN, MX, NO, NZ, PL, RO, SG, SI, SK, TR, TT, UA, US, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>In English translation (filed in Swedish).</i>	

(54) Title: DEVICE FOR WEIGHT OUTBALANCING IN CONNECTION WITH LIFTS

(57) Abstract

Device for outbalancing a lifting tool and a load separately in connection with a lift. The lifting tool will be outbalanced with a counterweight, the load will be outbalanced by the force of a cylinder.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Device for weight outbalancing in connection with lifts

The invention relates to a lifting equipment that outbalances a weight. The balancing is intended to work independent from the size of weight within the working area.

Background to the invention

Today it is time-wasting to lift easy details with facilities. One wish is to find a lifting tool with the same movement speed as the hand of a human being. When an object is to be lifted with the help of a manipulator the following forces must be transmitted:

Force F1 weight of the detail

Force F2 weight of the lifting tool

Force F3 inertia of the manipulator

The total lifting force F will accordingly be $F = F1 + F2 + F3$.

In a normal handling cycle appr. 50% of the time will handle the forces $F1 + F2 + F3$ and appr. 50% of the time will handle $F2 + F3$.

Purpose of the invention

To effect a lifting tool that follows the movements of your hand. The invention is below mentioned "manipulator".

Drawings

Figures 1-4 show the working function for the lifting device that outbalances a weight.

Figures 5-6 show the lifting device from the front and from the side.

Details on the drawing figures 5-6

1. Power plant e.g. electromagnet, electromagnetic field, pneumatic-hydraulic cylinder, mechanical arm and so on.
2. Slide valve.
3. Venting hole in the cylinder axis.
4. Cord.
5. Cylinder axis.
6. Slide with wheel.
7. Fore cylinder chamber.
8. Balance weight
9. Head cylinder.
10. Rear cylinder chamber.
11. Proportional valve.
12. Wheel I.
13. Wheel II.
14. Fastening point of cord.
15. Lifting tool.

Head components of the device

- | | |
|---|--|
| A | Cylinder (9) |
| B | A guide (6) with balance weight is mounted on the cylinder axis. |
| C | Proportional valve (11). |
| D | Cord (4) with wheels (12 + 13). |

Function description

The invention has two different force suppliers.

- A Counterweight that outbalances the lifting tool F2.
- B Force from the cylinder that outbalances the lifted detail F1.

The manipulator has two working modes:

- 1) When moving the manipulator without load but with a lifting tool F2
- 2) When moving the manipulator with load $F1 + F2$.

Function according to drawing figures 1-4.

The drawing shows a cylinder axis (5) that is drawn out in its head position.

A guide is mounted on the cylinder axis, that is able to run up and down.

On the guide there is a counterweight (8).

One or several wheels (12 + 13) are mounted, depended on the transmission desired. The cord (4) has been drawn through the wheels and attached to its end in point 14. The other end of the cord has been connected to the lifting tool (15). When the lifting tool moves into a vertical level it will consequently be outbalanced.

Lift of a detail

The cylinder axis is in its head position, as there will be a common pressure on both cylinder chambers (7 + 10). The space in the front chamber (7) is somewhat smaller owing to the surface of the axis, that will cause the axis to be fully projected. When there is a signal, the pressure in the lower cylinder chamber (10) will slowly fall. The axis (5) will consequently move down. The lower part of the slide valve (2) meets the

upper part of the slide (6). The slide (6) will be pressed down and the load (15) will be lifted. The pressure in the cylinder chamber (7 and 10 respectively) is constant, which results in the lifting force being constant in the whole operating range.

Drawing figures 1-4 show the working function in each routine

- Fig. 1 Detail term
- Fig. 2 The slide (6) can move up and down towards the cylinder axis without any effect when the axis is fully suspended. This function is normally used when the lifting tool moves without any load.
- Fig. 3 Signal has been given that a lift of a detail shall start. Power plant (1) pushes the slide valve (2) down, which results in opening of the same. Exhaustion of the cylinder chamber (10) will start parallel with the exhaustion through the valve of the cylinder chamber (10).
- Fig. 4 When the slide valve (2) meets the slide (6), the slide valve will be pushed up and closed. The exhaustion through the cylinder axis will cease. The exhaustion through the cylinder chamber (10) continues till there is a pressure desired.

Patent Claims

1. A device to be used in order to select two different lifting operations in a lifting manipulator:

1) lift of a lifting tool, 2) lift of a lifting tool incl. a load. These two operations shall be controlled by the motion speed of your hand within the operating range

characterized in

that a counterweight (8) outbalances a lifting tool (15) that is mounted in the end of a lifting cord. The cord is drawn through one or several wheels (12 + 13) depending on the exchange desired. When lifting a lifting tool incl. a load, a cylinder with an arranged piston and cylinder axis will be activated. The cylinder axis will actuate on the cylinder axis a movable slide (6) with an arranged wheel and the counterweight (8) and applies a force..

2. Device within the patent claim 1.

characterized in

that a cylinder (5) during the lift of a lifting tool only has a common pressure on its two chambers (7 + 10), which are divided by the piston. When lifting the lifting tool incl. a load the rear chamber will be exhausted to the pressure desired.

3. Device within the patent claim 1.

characterized in

that the cylinder axis (5) is hollow and provided with a valve (2), that will start an exhaustion when pressed down, which results in the rear cylinder

chamber being emptied and the cylinder axis being moved into the cylindric block.

When the valve (2) meets the slide (6) it will be pressed upwards and the exhaustion will stop. The movement of the cylinder axis will stop.

1 / 2




Fig.1




Fig.2




Fig.3




Fig.4




FIG. 5

SUBSTITUTE SHEET (RULE 26)

FIG. 6

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/00912

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: B66C 23/72

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: B66C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3259351 A (R.A.OLSEN), 5 July 1966 (05.07.66), figure 1 --	1
A	US 3259352 A (R.A.OLSEN), 5 July 1966 (05.07.66), figure 1, abstract --	1
A	US 3615067 A (N.G.GOUDREAU), 26 October 1971 (26.10.71), figure 1, abstract --	1
A	US 3721416 A (N.G.GOUDREAU), 20 March 1973 (20.03.73), figure 1, abstract -- -----	1



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

28 August 1997

Date of mailing of the international search report

01-09-1997

Name and mailing address of the ISA/
Swedish Patent Office

Authorized officer

06/08/97

PCT/SE 97/00912

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
US	3259351	A	05/07/66	NONE		
US	3259352	A	05/07/66	NONE		
US	3615067	A	26/10/71	DE	1959456 A,B,C	24/09/70
				FR	2033711 A	04/12/70
				GB	1250082 A	20/10/71
				SE	366003 B	08/04/74
US	3721416	A	20/03/73	AU	2289595 A	10/11/95
				AU	3325971 A	15/03/73
				CA	945503 A	16/04/74
				DE	2160177 A	08/06/72
				EP	0759068 A	26/02/97
				FR	2116553 A,B	13/07/72
				GB	1335439 A	31/10/73

BEST AVAILABLE COPY